

Metric		Imperial			Rotor Specs					Stator Specs (Standard Connections)			
Meters Day/100RPM	Lift (Meters)	Barrels Day/100RPM	Lift (Feet)	Rated Pressure (psi)	Minimum Tubing for Rotor Drift	Max OD (inches)	Rotor Pin Connection	Rotor (XL) Overall Length		Barrel OD (Inches)	Top Connection	Stator Overall Length including Tag Bar	
								Inches	meters			Inches	meters
6	600	38	2000	852	2 3/8" (1.995")	1.625	7/8" API	64	1.626	3"	Threaded Collars 2 7/8" EUE 3.46" OD or 3 1/2" EUE 4.18" OD	76	1.930
	900		3000	1278				88	2.235			100	2.540
	1200		4000	1704				112	2.845			124	3.150
	1500		5000	2130				136	3.454			148	3.759
	1800		6000	2556				160	4.064			172	4.369
28	600	180	2000	852	2 3/8" (1.995")	1.625	7/8" API	176	4.470	3"	Welded Collar 2 3/8" EUE 3.0" OD	188	4.775
	900		3000	1278				248	6.299			260	6.604
	1200		4000	1704				320	8.128			332	8.433
	1500		5000	2130				392	9.957			404	10.262
	600		2000	852				82	2.083			94	2.388
10	1200	60	4000	1704	2 3/8" (1.995")	1.900	7/8" API	150	3.810	3.5"	Threaded Collar 3 1/2" EUE 4.18" OD or Welded Collar 2 7/8" EUE 3.5" OD	162	4.115
	1800		6000	2556				218	5.537			230	5.842
	2400		8000	3408				286	7.264			298	7.569
	700		2300	994				101	2.565			113	2.870
15	1000	95	3300	1420	2 3/8" (1.995")	1.900	7/8" API	137	3.480	3.5"	Welded Collar 2 7/8" EUE 3.5" OD	149	3.785
	1400		4600	1988				185	4.699			197	5.004
	1800		6000	2556				233	5.918			245	6.223
	2100		7000	2982				269	6.833			281	7.137
	2800		9200	3976				353	8.966			365	9.271
	1500		5000	2130				107	2.718			90	2.286
8 Hybrid	1800	50	6000	2556	2 7/8" (2.441")	1.875	7/8" API	125	3.175	3.75"	3 1/2" EUE Threaded Collar 4.18" OD	108	2.743
	1500		5000	2130				125	3.175			108	2.743
12 Hybrid	1800	75	6000	2556	2 7/8" (2.441")	2.000	1" API	147	3.734	3.75"	3 1/2" EUE Threaded Collar 4.18" OD	130	3.302
	600		2000	852				71	1.803			76	1.930
18	900	110	3000	1278	2 7/8" (2.441")	2.100	1" API	98	2.489	3.75"	3 1/2" EUE Threaded Collar 4.18" OD	103	2.616
	1200		4000	1704				125	3.175			130	3.302
	1500		5000	2130				152	3.861			157	3.988
	1800		6000	2556				179	4.547			184	4.674
	600		2000	852				104	2.642			109	2.769
27	900	170	3000	1278	2 7/8" (2.441")	2.100	1" API	147	3.734	3.75"	3 1/2" EUE Threaded Collar 4.18" OD	152	3.861
	1200		4000	1704				190	4.826			195	4.953
	1500		5000	2130				233	5.918			238	6.045
	1800		6000	2556				276	7.010			281	7.137
	2100		7000	2982				319	8.103			324	8.230
	600		2000	852				125	3.175			130	3.302
35	900	220	3000	1278	2 7/8" (2.441")	2.100	1" API	179	4.547	3.75"	3 1/2" EUE Threaded Collar 4.18" OD	184	4.674
	1200		4000	1704				233	5.918			238	6.045
	1500		5000	2130				287	7.290			292	7.417
	1800		6000	2556				341	8.661			346	8.788
	600		2000	852				125	3.175			130	3.302
45	900	285	3000	1278	2 7/8" (2.441")	2.200	1" API	179	4.547	3.75"	3 1/2" EUE Threaded Collar 4.18" OD	184	4.674
	1200		4000	1704				233	5.918			238	6.045
	1500		5000	2130				287	7.290			292	7.417
	1800		6000	2556				341	8.661			346	8.788
	600		2000	852				161	4.089			166	4.216
60	900	380	3000	1278	2 7/8" (2.441")	2.200	1" API	233	5.918	3.75"	3 1/2" EUE Threaded Collar 4.18" OD	238	6.045
	1200		4000	1704				305	7.747			310	7.874
	1500		5000	2130				377	9.576			382	9.703
	1800		6000	2556				449	11.405			454	11.532
	400		1200	568				125	3.175			137	3.480
85	600	535	2000	852	2 7/8" (2.441")	2.340	1" API	172	4.369	4.33"	4" NUE Weld-on Collar (4.5" OD)	184	4.674
	800		2800	1136				233	5.918			245	6.223
	1000		3300	1420				287	7.290			299	7.595
	1200		4000	1704				341	8.661			353	8.966
	1400		4600	1988				395	10.033			407	10.338

Metric		Imperial			Rotor Specs					Slimhole Stator Connections			
Meters Day/100RPM	Lift (Meters)	Barrels Day/100RPM	Lift (Feet)	Rated Pressure (psi)	Minimum Tubing for Rotor Drift	Max OD (inches)	Rotor Pin Connection	Rotor (XL) Overall Length		Barrel OD	Top Connection	Stator Overall Length including Tag Bar	
								Inches	meters			Inches	meters
18	600	110	2000	852	2 7/8" (2.441")	2.100	1" API	71	1.803	3.75"	48" Orbit Tube c/w 2 7/8" EUE Conn	122	3.099
	900		3000	1278				98	2.489			149	3.785
	1200		4000	1704				125	3.175			176	4.470
	1500		5000	2130				152	3.861			203	5.156
	1800		6000	2556				179	4.547			230	5.842
27	600	170	2000	852	2 7/8" (2.441")	2.100	1" API	104	2.642	3.75"	48" Orbit Tube c/w 2 7/8" EUE Conn	155	3.937
	900		3000	1278				147	3.734			198	5.029
	1200		4000	1704				190	4.826			241	6.121
	1500		5000	2130				233	5.918			284	7.214
	1800		6000	2556				276	7.010			327	8.306
	2100		7000	2982				319	8.103			370	9.398
35	600	220	2000	852	2 7/8" (2.441")	2.100	1" API	125	3.175	3.75"	48" Orbit Tube c/w 2 7/8" EUE Conn	176	4.470
	900		3000	1278				179	4.547			230	5.842
	1200		4000	1704				233	5.918			284	7.214
	1500		5000	2130				287	7.290			338	8.585
	1800		6000	2556				341	8.661			382	9.703
45	600	285	2000	852	2 7/8" (2.441")	2.200	1" API	125	3.175	3.75"	48" Orbit Tube c/w 2 7/8" EUE Conn	176	4.470
	900		3000	1278				179	4.547			230	5.842
	1200		4000	1704				233	5.918			284	7.214
	1500		5000	2130				287	7.290			338	8.585
	1800		6000	2556				341	8.661			382	9.703
60	600	380	2000	852	2 7/8" (2.441")	2.200	1" API	161	4.089	3.75"	48" Orbit Tube c/w 2 7/8" EUE Conn	212	5.385
	900		3000	1278				233	5.918			284	7.214
	1200		4000	1704				305	7.747			356	9.042
	1500		5000	2130				377	9.576			445	11.303
	1800		6000	2556				449	11.405			517	13.132
85	400	535	1200	568	2 7/8" (2.441")	2.340	1" API	125	3.175	4.33"	36" Orbit Tube c/w 3 1/2" EUE (can be swedged to 2 7/8" if required)	171	4.343
	600		2000	852				172	4.369			218	5.537
	800		2800	1136				233	5.918			279	7.087
	1000		3300	1420				287	7.290			333	8.458
	1200		4000	1704				341	8.661			387	9.830
	1400		4600	1988				395	10.033			441	11.201

Metric		Imperial			Rotor Specs					Stator Specs			
Meters Day/100RPM	Lift (Meters)	Barrels Day/100RPM	Lift (Feet)	Rated Pressure (psi)	Minimum Tubing for Rotor Drift	Max OD (inches)	Rotor Pin Connection	Rotor (XL) Overall Length		Barrel OD	Top Connection	Stator Overall Length including Tag Bar	
								Inches	meters			Inches	meters
80	900	500	3000	1278	3 1/2" (2.992")	2.450	1" API	233	5.918	4.33"	36" Orbit tube c/w 3 1/2" EUE Internal Thread (4.25" OD)	270	6.858
	1200		4000	1704				305	7.747			342	8.687
	1500		5000	2130				377	9.576			414	10.516
100	700	630	2500	994	3 1/2" (2.992")	2.450	1" API	233	5.918	4.33"	36" Orbit tube c/w 3 1/2" EUE Internal Thread (4.25" OD)	270	6.858
	900		3000	1278				305	7.747			342	8.687
	1200		4000	1704				377	9.576			414	10.516
	1500		5000	2130				449	11.405			486	12.344
120	800	755	2800	1136	3 1/2" (2.992")	2.800	1 1/8" API	212	5.385	5"	40" Orbit tube c/w 3 1/2" EUE Weld-on Collar (5" OD)	258	6.553
	1000		3300	1420				262	6.655			308	7.823
	1200		4000	1704				312	7.925			358	9.093
160	600	1000	2000	852	3 1/2" (2.992")	2.800	1 1/8" API	212	5.385	5"	40" Orbit tube c/w 3 1/2" EUE Weld-on Collar (5" OD)	258	6.553
	900		3000	1278				312	7.925			358	9.093
	1200		4000	1704				412	10.465			458	11.633
200	500	1250	1650	710	3 1/2" (2.992")	2.800	1 1/8" API	212	5.385	5"	40" Orbit tube c/w 3 1/2" EUE Weld-on Collar (5" OD)	258	6.553
	750		2500	994				312	7.925			358	9.093
	1000		3300	1420				412	10.465			458	11.633